Deye Smart Transmitter (TX)

SUN-SMART-TX01
SUN-SMART-TXU1



Wide Compatibility

- Compatible with the all Deye hybrid inverters

Seamless Integration

- Supports 10 Smart Switches/Plugs, 2 CTs & 1 EV Charger

LoRa Communication

- Low latency
- Long-range communication
- Offline operation

Simple Setup

- Easy installation
- Quick pairing with Deye hybrid inverters

Technical Data

Model	SUN-SMART-TX01	SUN-SMART-TXU1
Electrical Parameters		
Input Voltage	DC 5V	
Communication		
Communication Model	LoRa	
Communication Distance	≈200m (Barrier free)	
Basic Parameters		
Operating Temperature Range	-40 to +60℃	
Permissible Ambient Humidity	0-100%	
Ingress Protection(IP) Rating	IP20 (After installation IP65)	
Allowable Altitude	≤4000	
Product size (WxHxD)	137.8x31.3x31.3mm	
Weight	45.8g	
Warranty	2 Years	
Standard	IEC/EN 62368-1	
LoRa Parameters		
Frequency Range	863MHz-870MHz	920MHz-928MHz
Antenna	Built-in	
Antenna Gain	0.56dBi	

Ningbo Deye Inverter Technology Co., Ltd.
Address: No. 26 South YongJiang Road, Daqi, Beilun, NingBo, Zhejiang, China. | Tel: +86 (0)574 86228841 | E-mail: market@deye.com.cn

deye.shop

Поддержка на русском — deye.shop

Официальный дилер Deye в России — ООО «НТ»

Мы отвечаем на русском языке по любому оборудованию Deye из этого документа.

- Подберём инвертор и аккумуляторы под ваш дом или объект.
- Ответим на вопросы по монтажу, настройке и кодам ошибок.
- Поможем с гарантийным обращением.

Телефон	8 (800) 201-76-60, звонок по России бесплатный
Техническая поддержка	support@deye.shop
Заказы и счета	zakaz@deye.shop
Сайт	deye.shop

На сайте — документы на русском, цены с НДС и наличие на складах в Ростове-на-Дону, Подмосковье и Краснодаре. Работаем в будни с 9:00 до 18:00 по Москве.